



**safety-kleen** MAKE GREEN WORK

**ECOPOWER® BLENDED OIL PRODUCTS AND FLUIDS**



# EP INDUSTRIAL GEAR OIL

**ECOPOWER® EP Industrial Gear Oils** are specifically formulated to hold up under extreme high pressure in all types of gear sets excluding built-in variable speed friction drives. Approved for use in Chrysler and General Motors. Increase the life of your heavily loaded or shock loaded bearings and gear sets with EP Industrial Gear Oils.

Since ECOPOWER® is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates “in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products”
- Section 6002 of RCRA that requires federal agencies to “procure such items composed of the highest percentage of recovered materials practicable”
- Federal Regulation 23.4 that requires Federal Agencies to “use recovered materials to the maximum extent practicable”

## TYPICAL PROPERTIES

ECOPOWER®	ISO GRADE	68	100	150	220	320	460
AGMA Grade		2EP	3EP	4EP	5EP	6EP	7EP
Color		L 3.0	L 3.5	L 3.5	L 3.5	L 4.0	L 5.5
Specific Gravity 15.6°C (60°F)		0.872	0.875	0.881	0.885	0.888	0.892
Kinematic Viscosity							
cSt @ 40°C		66.2	100.5	152.0	221.6	320.0	460.0
cSt @ 100°C		8.9	11.8	15.4	19.5	28.0	30.0
Viscosity Index		109	106	102	100	99	95
Flash Point, °C		233	238	242	246	248	252
Pour Point, °C		-30	-27	-18	-12	-9	-6
Demulsibility D1401		Pass	Pass	Pass	Pass	Pass	Pass
Timken OK Load, lbs		65	65	65	65	65	65
FZG Pass Stage		12	12	12	12	12	12
Copper Corrosion		1B	1B	1B	1B	1B	1B

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. BYU41