

ECOPOWER® R&O OILS

ECOPOWER® R&O Oils contain an inhibitor that protects against rust, corrosion and deposit formation with equipment exposed to humidity or water. R&O also minimizes sludge, varnish and emulsions for increased equipment life and reduced operating costs. These versatile, specialized oils meet the requirements of industry and OEM specifications listed below.

Since ECOPOWER® is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

TYPICAL PROPERTIES

ECOPOWER®	ISO VG	22	32	46	68	100	150	220
Color		L 1.0	L 1.0	L 1.5	L 2.5	L 3.0	L 5.0	L 5.5
Specific Gravity (60°F)		0.855	0.856	0.859	0.865	0.876	0.879	0.882
Kinematic Viscosity	cSt @ 40°C	22.1	32.2	43.5	65.9	94.7	144.5	209.4
	cSt @ 100°C	4.4	5.6	6.8	9.0	11.1	14.7	18.8
Viscosity Index		106	112	113	112	102	101	100
Flash Point, °C		204	222	244	250	256	260	264
Pour Point, °C		-39	-33	-33	-30	-18	-12	-9
Water Separability (@ 30 min)		40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0
MAG Approvals		-	P-38	P-55	P-54	-	-	-

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. 0514