



safety-kleen MAKE GREEN WORK

ECOPOWER[®] BLENDED OIL PRODUCTS AND FLUIDS

**ECO
POWER**
ECO-FRIENDLY MOTOR OIL

SPINDLE OILS

ECOPOWER[®] Spindle Oils are formulated for use in high speed, light to moderate load spindle applications where heat dissipation as well as rust and oxidation inhibiting properties are important.

Since ECOPOWER[®] is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates “in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products”
- Section 6002 of RCRA that requires federal agencies to “procure such items composed of the highest percentage of recovered materials practicable”
- Federal Regulation 23.4 that requires Federal Agencies to “use recovered materials to the maximum extent practicable”

TYPICAL PROPERTIES

ECOPOWER [®]	ISO GRADE	22	32
Color		L 1.0	L 1.0
Specific Gravity 15.6°C (60°F)		0.855	0.861
Kinematic Viscosity			
cSt @ 40°C		22.0	32.1
cSt @ 100°C		4.4	5.6
Viscosity Index		110	111
Flash Point, °C		208	220
Pour Point, °C		-36	-33
Demulsibility D1401		Pass	Pass
Rust Characteristics D665		Pass	Pass
Copper Corrosion		1B	1B

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYU74